





## **NOTES**

- I. CONCRETE SHALL BE CONCRETE MIX NO. 6 (4500 PSI).
- 2. REINFORCEMENT SHALL BE PLAIN OR EXPOXY COATED 4" X 4" W4.0 X W4.0 WELDED WIRE FABRIC.
- 3. ONE CONNECTOR PIN SHALL BE FURNISHED WITH EACH BARRIER. SEE STD. MD 104.01-41 FOR DETAILS OF CONNECTOR PIN.
- 4. THE APPROACH PLATE SHALL BE FABRICATED USING 1/2" THICK STEEL PLATE BENT OR WELDED TO THE CONFIGURATION SHOWN ON STD. MD 104.01-61 AND GALVANIZED AFTER FABRICATION. THE APPROACH PLATE SHALL BE ANCHORED TO THE PRECAST TEMPORARY BARRIER TRANSITION AND TO THE EXISTING CONCRETE BARRIER IN THE FIELD TO ACHIEVE PROPER PLACEMENT AND HOLE ALIGNMENT WITH 6 EXPANSION ANCHORS (EACH END) AND 1/8" Ø HEX HEAD BOLTS.
- 5. THE COST OF THE APPROACH PLATE, ANCHORS, BOLTS, CONNECTOR PIN, LABOR, ETC. SHALL BE INCIDENTAL TO THE UNIT PRICE PER EACH FOR PRECAST TEMPORARY JERSEY SHAPE CONCRETE BARRIER TRANSITION LEFT SIDE APPROACH.

I	SPECIFICATION 104	CATEGORY CODE ITEMS				Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES PRECAST TEMPORARY JERSEY SHAPE CONCRETE		
	APPROVED Kik G. M. COLL DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT							
I		REVISIONS		APPROVAL • FEDERAL HIGHWAY ADMINISTRATION		TRAFFIC BARRIER TRANSITION-LEFT		
ı			_	APPROVAL REVISED	9-23-03 3-31-04	SIDE APPROACH		
l	State Highway  Administration	REVISED REVISED	_	REVISED REVISED		STANDARD NO.	MD	104.01–44